


Poly CCX 400 Business Media Phone for Microsoft Teams and PoE-enabled

"Entry-level" just got sweeter

The Poly CCX 400 is an entry-level business phone that's easy to use. Its interface is simple and intuitive. And contacts and meetings are one swipe or one tap away on a color touch screen.



*Product image may differ from actual product

Sound your best

Hear every nuance with Poly HD Voice and Poly Acoustic Clarity technologies. Poly Acoustic Fence technology reduces distracting background noise and makes calling a pleasure.

Stylish, ultra-usable design

Enjoy the ergonomic design and the intuitive user touchscreen interface that saves you the hassle of learning new features and functions. When a phone is this easy, better collaboration and productivity aren't far behind.

Audio clarity

Conversations stay clear with Poly HD Voice and Poly Acoustic Clarity technologies.

Distraction-free calls

Reduce distracting background noise with Poly Acoustic Fence technology.

Touchscreen controls

Contacts and meetings are easily accessible via the color touchscreen with 5" multi-touch LCD display.

IT friendly

Easy for IT to manage with provisioning and management of telephony deployment and support.

Datasheet

Poly CCX 400 Business Media Phone for Microsoft Teams and PoE-enabled

Specifications



Compatible with

Compatible operating systems: Android 9

Display

Aspect ratio: 16:9

Native resolution: 720 x 1280

Panel technology: Color LCD

Display size (diagonal): 5"

Display size (diagonal, metric): 12.7 cm (5")

Touch-enabled: Gesture-based, multi-touch capable touchscreen

Connectivity and communications

External I/O ports:

1 USB 2.0 Type-A (for media and storage applications)

2 RJ-45 (10/100/1000BASE-TX Mbps)

Battery

Power features:

Built-in auto sensing IEEE 802.3af Power over Ethernet (Class 0)

13 W (maximum)²

User interface features

Languages:

Arabic; Chinese; Czech; Danish; Dutch; English; French; German; Hungarian; Italian; Japanese; Korean; Norwegian; Polish; Portuguese; Romanian; Russian; Slovenian; Spanish; Swedish

Audio

Audio features:

Poly HD Voice

Poly Acoustic Clarity technology provides full duplex conversations, acoustic echo cancellation, and background noise suppression

Poly Acoustic Fence technology eliminates background noise when using a handset or wired headset

Poly NoiseBlockAI technology removes most background noise when using the speakerphone

TIA-920 wideband audio, type 1 compliant (IEEE 1329 full duplex)

Individual volume settings with visual feedback for each audio path

Voice activity detection

Comfort noise generation

DTMF tone generation (RFC 2833 and in-band)

Low delay audio packet transmission

Adaptive jitter buffers

Frequency response (microphone): 150 Hz to 7 kHz

Audio codecs:

G.711 (A-law and μ -law)

G.722

G.722.1

G.729AB

iLBC

OPUS

Environmental

Certifications and compliances: AS/NZS 62368-1:17; Australia RCM; Brazil ANATEL; CISPR22 Class B; EEA; CE Mark; EN55024; EN55032 Class B; EN 62368-1; FCC Part 15 (CFR 47) Class B; IEC 60950-1 & IEC 62368-1; ICES-003 Class B; Japan MIC/VCCI; NZ Telepermit; Saudi Arabia CITC; So. Africa ICASA; So. Korea KC; UL 62368-1; VCCI Class B; Canada ICES and NRTL; China RoHS 2.0; Indonesia SDPPI; Mexico NYCE; Russia Customs Union

Operating humidity range: 5 to 95%

Operating Temperature Range (Celsius) / Operating Temperature Range (Fahrenheit): 0 to 40°C / 32 to 104°F

Storage temperature range (Celsius) / Storage temperature range (Fahrenheit): -40 to 70°C / -40 to 158 °F

Certifications

Special features:

Unicode UTF-8 character support

Adjustable desk stand (2 positions)

Applications supported

Management software:

Poly Lens

Poly Zero Touch Provisioning

Polycom Device Management Service for Service Providers (PDMS-SP) Cloud Management

Web UI to device IP address

Display features

Adjustable font size selection (regular, medium, large); Screensaver; Voicemail support; Normal and dark mode; Digital picture frame

Security

Security management:

8021X Authentication and EAPOL Media encryption via SRTP

Digest authentication

Encrypted configuration files

HTTPS secure provisioning

Password login

Support for signed software executables

Support for URL syntax with password

Transport Layer Security (TLS)

SRTP media encryption using AES 256 bits

Network

Supported network protocols:

Manual or dynamic host configuration protocol (DHCP) network setup

10/100/1000 Base-TX across LAN and PC ports

Conforms to IEEE802.3-2005 (Clause 40) for physical media attachment

Conforms to IEEE802.3-2002 (Clause 28) for link partner auto-negotiation

IPv6

VoIP features:

24 lines (SIP registrations)

IETF SIP (RFC 3261 and companion RFCs)

Poly CCX 400 Business Media Phone for Microsoft Teams and PoE-enabled

Specifications



Headset and handset compatibility

Headset ports:

1 RJ-9

1 Electronic Hook Switch (EHS) port for optional adapter

Headset and handset compatibility:

Compatible with commercially available TTY adapter equipment

Compliant with ADA Section 508 Subpart B 1194.23 (all)

Hearing aid compatibility to ITU-T P.370 and TIA 504A standards

Hearing aid compatible (HAC) handset for magnetic coupling to hearing aids

USB Type-A headset support

Telephony and call handling features

Telephony and call handling features:

Busy Lamp Field (BLF)

Call timer and call waiting

Caller ID enable/disable

Distinctive incoming call treatment/call waiting

Do not disturb function

One-touch speed dial, redial

Shared call/bridged line appearance

Automatic off-hook call placement (hot dialing)

Call media recording/playback

Automatic/remote answer on headset using electronic hook-switch

Call hold/resume, diversion (forward), transfer (consultation, blind), pickup

Calling, called, connected party identification

Call forward for shared lines

Private hold for shared lines

Call logs (missed, received, placed)

Local contact directory

Create local contact from call log

Corporate directory

Call server redundancy (failover)

SBC line registration

Conference bridging

Local call forwarding (all, busy, no answer) with destination shown on idle display

Automatic call distribution (ACD)

Automatic answer (intercom)

Call park/retrieve

Directed call pickup

Group call pickup

Hunt group - sequential calling

Last call return

Auto-answer a page with a muted microphone

PTT and Multicast group

Exchange Calendar Integration

Flexible line keys

Key system emulation

STIR/SHAKEN Caller ID validation

Voice Quality Monitoring (VQMon)¹

Weight and dimensions

Product Primary Color: Black

Package dimensions (Imperial): 8.7 x 9.6 x 2.7 in

Package dimensions (metric): 22.2 x 24.3 x 6.9 cm

Package weight (Imperial): 2.23 lb

Package Weight (metric): 1004 g

UPC number: 197497506242

Product number: 848Z8AA

Country of origin

Country of origin: Made in China

Warranty

Poly standard one-year limited warranty

What is in the box

Console

Desk stand

Handset with handset cord

Network (LAN) cable-CAT-5E

Setup sheet

Key Selling Points Footnotes

¹ Visit <https://www.poly.com/us/en/products/phones/ccx/400> for more detail.

Technical Specifications Footnotes

¹ Most software-enabled features must be supported by the service provider platform. Please contact your IP PBX/softswitch vendor or service provider for a list of supported features. ² External universal AC/DC adapter, 5 VDC, 3 A, 15 W (sold separately).